

**LIST OF CURRENT CLAIMS**

1. (Currently Amended) An assembly (10) having information (16) to be secured, such information exemplified by as a coding, identification, PIN number or the like, comprising:
  - [[ - ]] an object (20) on which the information (16) is to be secured is provided, and
  - [[ - ]] a security cover sticker (18) having a base area smaller than the object (20) and covering the information (16) to be secured, wherein, characterized by
  - [[ - ]] an additional layer (30, 32, 42, 46) ~~which~~ is disposed between the object (20) and the information (16) to be secured, and
  - [[ - ]] said additional layer comprising ~~which comprises~~ an ink layer or lacquer layer (30, 34, 40) disposed directly on the object (20), and
  - [[ - ]] the adhesive ~~power~~ strength of the additional layer (30, 32, 42, 46) to the cover sticker (14) ~~being~~ is greater at least in partial areas than the adhesive ~~power~~ strength of the additional layer (30, 32, 42, 46) to the object (20).
2. (Currently Amended) ~~The~~ An assembly (10) according to claim 1, ~~characterized in that~~ wherein the information (16) to be secured is printed on the additional layer (30, 32, 42, 46) by an ink jet process.
3. (Currently Amended) ~~The~~ An assembly (10) according to claim 1 ~~or 2~~, ~~characterized in that~~ wherein the information (16) to be secured is applied to the additional layer (30, 32, 42, 46) in black.
4. (Currently Amended) ~~The~~ An assembly (10) according to claim 1, wherein ~~any of claims 1 to 3, characterized in that~~ the additional layer is formed by an ink layer (30).

5. (Currently Amended) The An assembly (10) according to claim 1, wherein ~~any of claims 1 to 3, characterized in that~~ the additional layer is formed by a multi-ply layer (32, 42, 46) and comprises at least one upper ink layer (36) and at least one lacquer layer (34) disposed between the object (20) and the upper ink layer (36) as the ink layer or lacquer layer.
6. (Currently Amended) The An assembly (10) according to claim 5, wherein ~~characterized in that~~ the lacquer layer is formed by a UV lacquer (34).
7. (Currently Amended) The An assembly (10) according to claim 4, wherein ~~any of claims 4 to 6, characterized in that~~ the ink layer (30, 36) located under the information (16) to be secured is formed by a monochrome ink layer; ~~preferably a white ink layer.~~
8. (Currently Amended) The An assembly (10) according to claim 4, wherein ~~any of claims 4 to 7, characterized in that~~ the color of the ink layer (30, 36) located under the information (16) to be secured is coordinated with the color of the information (16) to be secured to produce high contrast between the information (16) to be secured and the ink layer (30, 36) located thereunder.
9. (Currently Amended) The An assembly (10) according to claim 5, wherein ~~any of claims 5 to 8, characterized in that~~ the multi-ply layer (46) comprises a second ink layer (44) disposed between the lacquer layer (34) and the upper ink layer (36) located under the information (16) to be secured.
10. (Currently Amended) The An assembly (10) according to claim 9, ~~characterized in that~~ wherein the second ink layer (44) has an irregular pattern.

11. (Currently Amended) The An assembly (10) according to claim 9 ~~or 10~~, wherein ~~characterized in that~~ the second ink layer (44) contains blind information whose character corresponds to the information (16) to be secured.
12. (Currently Amended) The An assembly (10) according to claim 1, wherein ~~any of claims 1 to 11, characterized in that~~ the adhesive power strength of the additional layer (30, 32, 42, 46) to the cover sticker (14) is greater than the adhesive power strength of the additional layer (30, 32, 42, 46) to the object (20).
13. (Currently Amended) The An assembly (10) according to claim 1, wherein ~~any of claims 1 to 11, characterized in that~~ the adhesive power strength of the additional layer (30, 32, 42, 46) to the cover sticker (14) is greater than the adhesive power strength of the additional layer to the object (20) in first areas, and the adhesive power strength of the additional layer (30, 32, 42, 46) to the cover sticker (14) is smaller than the adhesive power strength of the additional layer (30, 32, 42, 46) to the object (20) in second areas.
14. (Currently Amended) The An assembly (10) according to claim 13, wherein ~~characterized in that~~ the first and second areas form a fine-scale structure.
15. (Currently Amended) The An assembly (10) according to claim 13 ~~or 14~~, wherein ~~characterized in that~~ the first and second areas form an irregular structure.
16. (Currently Amended) The An assembly (10) according to claim 13, wherein ~~any of claims 13 to 15, characterized in that~~ the size and shape of the first and second areas are coordinated with the information (16) to be secured

such that it the information is no longer decipherable after removal of the cover sticker (14).

17. (Currently Amended) The ~~An~~ assembly (10) according to claim 13, wherein ~~any of claims 13 to 16, characterized in that~~ the additional layer (42) has means (38, 40) for effecting locally different adjustment of adhesive strength ~~power~~.
18. (Currently Amended) The ~~An~~ assembly (10) according to claim 17, wherein ~~characterized in that~~ the means for effecting locally different adjustment of adhesive power strength comprises ~~comprise~~ a non-stick lacquer (38) applied to the object (20) locally between the information (16) to be secured and the object (20).
19. (Currently Amended) The ~~An~~ assembly (10) according to claim 17 ~~or 18, wherein~~ characterized in that the means for effecting locally different adjustment of adhesive power strength comprises ~~comprise~~ an adhesion promoter (40) applied to the object (20) locally between the information to be secured and the object (20).
20. (Currently Amended) The ~~An~~ assembly (10) according to claim 17, wherein ~~any of claims 17 to 19, characterized in that~~ the means (38, 40) for effecting locally different adjustment of adhesive ~~power are~~ strength is applied to the object (20) by printing.
21. (Currently Amended) The ~~An~~ assembly (10) according to claim 1, wherein ~~any of claims 1 to 20, characterized in that~~ the additional layer (30, 32, 42, 46) is printed on the object (20).

22. (Currently Amended) ~~The~~ An assembly (10) according to claim 21, wherein ~~characterized in that~~ the additional layer (30, 32, 42, 46) is printed on the object (20) by ~~the~~ an offset process.
23. (Currently Amended) ~~The~~ An assembly (10) according to claim 1, wherein ~~any of claims 1 to 22, characterized in that~~ the information (16) to be secured is a character string, ~~in particular~~ exemplified by a secret number or PIN number.
24. (Currently Amended) ~~The~~ An assembly (10) according to claim 1, wherein ~~any of claims 1 to 23, characterized in that~~ the assembly (10) is a value document, ~~in particular~~ exemplified by a bank card, credit card, prepaid stored-value card such as a phonecard, or lottery ticket.
25. (Currently Amended) ~~The~~ An assembly (10) according to claim 1, wherein ~~any of claims 1 to 24, characterized in that~~ the cover sticker is an adhesive label, ~~in particular a scratch label (14).~~
26. (Currently Amended) ~~The~~ An assembly (10) according to claim 1, wherein ~~any of claims 1 to 25, characterized in that~~ the additional layer (30, 32, 42, 46) is formed on the object (20) in ~~the~~ a size of an information field (12) comprising the information (16) to be secured.
27. (Currently Amended) ~~The~~ An assembly (10) according to claim 1, wherein ~~any of claims 1 to 26, characterized in that~~ the cover sticker (14) has a ~~greater~~ larger base area than the additional layer.
28. (Currently Amended) A method for producing an assembly (10) with information (16) to be secured, exemplified by ~~such as~~ a coding, identification, PIN number or the like, comprising the steps: ~~characterized by the following steps:~~

- a) supplying an object (20) to be provided with the information,
  - b) applying an additional layer (30, 32, 42, 46) to the object (20) with a first, uniform or locally different adhesive power strength to the object (20), the additional layer comprising an ink layer or lacquer layer (30, 34, 40) disposed directly on the object (20),
  - c) applying the information (16) to be secured to the additional layer (30, 32, 42, 46), and
  - d) covering the information (16) to be secured with a security cover sticker (14) having a smaller base area than the object (20) and a second adhesive power strength to the additional layer (30, 32, 42, 46), the second adhesive power strength being greater at least in partial areas than the first adhesive power strength of the additional layer (30, 32, 42, 46) to the object (20).
29. (Currently Amended) The A method according to claim 28, including applying characterized in that an ink layer is applied as the additional layer in step b).
30. (Currently Amended) The A method according to claim 28, wherein: characterized in that in step b)
- b1) a lacquer layer which adjusts the adhesive power strength of the additional layer to the object is applied to the object as the ink layer or lacquer layer, and
  - b2) an ink layer is applied to the lacquer layer.
31. (Currently Amended) The A method according to claim 30, including: characterized in that in a step

- b3) applying a further ink layer with another color and/or another pattern is applied to the ink layer present.
32. (Currently Amended) The A method according to claim 28, wherein ~~any of claims 28 to 31, characterized in that~~ in step b) means for locally different adjustment of adhesive ~~power~~ strength are applied to the object, in particular a non-stick lacquer and/or an adhesion promoter is applied locally to the object.
33. (Currently Amended) The A method according to claim 28, wherein ~~any of claims 28 to 32, characterized in that~~ the layers applied in step b) are printed on, preferably printed by the an offset process.
34. (Currently Amended) The A method according to claim 28, wherein ~~any of claims 28 to 33, characterized in that~~ the information to be secured is printed on the additional layer by an ink jet process in step c).
35. (Currently Amended) The A method according to claim 28, wherein ~~any of claims 28 to 34, characterized in that~~ the additional layer is applied to the object in the size of an information field comprising the information to be secured.
36. (Currently Amended) The A method according to claim 28, wherein ~~any of claims 28 to 35, characterized in that~~ the cover sticker is selected so as to have a greater base area than the additional layer.